



Technical Data Sheet

ThermaTac

A flexible vinyl film coated with a removable pressure sensitive acrylic adhesive and backed with a two-sided poly coated lay flat release liner.

	67000 67004 White Removable	67001 67005 Frosty Clear Removable	67002 67006 White Ultra- Removable	67003 67007 Frosty Clear Ultra- Removable
Physical Properties				
Thickness (mil)				
Film	3.5	3.5	3.25	3.25
Adhesive	0.6 - 0.7	0.6 - 0.7	0.1 - 0.2	0.1 - 0.2
Liner	7.4	7.0	7.4	7.4
Weight (gsm)				
Film	220	150	220	150
Film & liner	314	297	285	244
Lb/Ream (cover)	117	111	85	91
Adhesion (oz/in)				
Stainless Steel	37	33	1.5	1.5
Acrylic	26	26	2.6	2.6
Glass	27	29	1.6	1.6
Polypropylene	21	21	0.6	0.6
Tack (gm)	230	240	30	30
Expected Exterior Life	2 years	2 years	2 years	2 years

Conditions for Use:

Service Temperature Range	-40°F to 176°F	-20°F to 176°F	-20°F to 176°F	-20°F to 176°F
Minimum Application Temp.	50°F	50°F	50°F	50°F
Storage Stability at 70°F and 50% RH	2 years	6 months	2 years	2 years

Compatibility and Best Practices:

Most Color/Black & White Production Scale Printers

- When printing films by high throughput, toner-based methods, the thick paper or film settings and recommended feed trays should be used where available. Please refer to the copier or printer manual for settings for film/heavyweight products.
- Customers must establish for themselves the optimum settings and paper path, since the thickness and weight of the material may be beyond the rates capabilities of some devices.
- Suitable for machines printing a minimum of 65+ sheets per minute.
- Heat and pressure can cause adhesives to migrate to the edge of the sheet. Our 1/16" clean strip edge is a safeguard against adhesive ooze going beyond the edge of the sheet and into sensitive digital equipment.

DISCLAIMER: The information provided herein is correct to the best of Nekoosa Coated Products' knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.



Technical Data Sheet

Applications:

Bumper Stickers
In-Store Labeling and Marketing
Parking Permits
Name Tags
Children's Stickers
Identification Labels
Seasonal Signs
Window Stickers
Oil Change Reminders

Cautions:

- This product removes cleanly from most shelf channels. However application environments and certain surfaces such as vinyl, glass, acrylic, polystyrene, or polycarbonate may cause increased adhesion and adhesive transfer.

Recycling:

Check with local recycling regulations for vinyl products

DISCLAIMER: The information provided herein is correct to the best of Nekoosa Coated Products' knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.